

LEAD-LINED FIRE DOORS

Special Purpose Lead-Lined Fire rated Doors

DESCRIPTION

Lead-lined Fire doorset designed to prevent the passage of radiation coming out of X-ray rooms, and also fire resistant to AS 1530.4.

APPLICATIONS

Lead lined radiation doors designed specifically for X-ray rooms in Hospital, Clinics, & Dental suites. These doors prevent the passage of unwanted radiation from exiting the X-ray rooms, and to protect the operators from potential harmful X-ray radiation.

FEATURES

- Up to 1.76mm Lead Equivalent shielding,
- Fire resistant up to 2hrs (FRL: -/120/30)
- Single or pair door configuration.
- Maximum door size: 2400 x 1200mm (each leaf)
- 48mm nom. door thickness.



HOW TO SPECIFY

"Door to be a Pyropanel Lead-lined fire rated door, 48mm nom. thick,-/120/30* FRL, mounted in Pyropanel packed steel door frame".

* denotes example - delete, change or specify as required

Pyropanel Developments Pty Ltd

Unit 1, 97 Lewis Rd, Wantirna South, Vic 3152

Ph: **(03) 9837 8500** Fax: (03) 9837 8550

Email: sales@pyropanel.com.au

Web: www.pyropanel.com.au

Distributed by:

Holland Fire Doors & Windows

23 Saggart Field Rd, Minto, NSW, 2566

Ph: **9603 8500**

Email: sales@hollandfiredoors.com.au